




Stiletto J

SURFACE MOUNTED | NON-DALI SERIES


Step into a realm of refined illumination with Stiletto, a collection that combines the allure of golden aesthetics with the precision of LED technology.

FEATURES & BENEFITS

- CRI > 90 as standard
- Color temperatures: 3000K, 4000K, 6500K
- Beam angles: 15°, 24°, 36°, 50°
- Luminaire efficiency: 60lm/W @4000K
- Output power: 7W
- Luminaires that can be DALI dimmable, by choosing an appropriate driver when configuring the system.

APPLICATION

High End Grocery & Supermarkets | Fashion Retailers | Art & Exhibitions | DIY



SPECIFICATIONS

Mounting type	Magnetic track mounted luminaires
Power consumption	7W
Dimensions	Lcable 519 x Ø50 x H47mm ± 1mm
Housing materials	Aluminium, Acrylic
IK code	IK00
Protection class	Safety class 1
Operating temperature [°C]	-20°C ... +40°C / -4F ... +104F
Operating humidity [%]	20 ÷ 90
DC Input [Vdc]	24 VDC
Lens angle [°]	15°, 24°, 36°, 50°
Lifespan [h]	50.000
Housing color	Brass, White, Black
Lumen maintenance	L70/B30@50.000h at 25°C
IP factor	IP20
Control option	-
Warranty [years]	3
Storage temperature range [°C]	10°C ... +30°C / 50°F ... +86°F
Emergency option	-

Light application	Standard
CRI	CRI90
CCT [K]	3000K, 4000K, 6500K


CRI - Color rendering, CCT - Color temperature

TOLERANCES

Luminous flux tolerances: -/+ 5%

Consumption tolerance: -/+ 5% for Non-DALI | -/+ 10% for Non-DALI & KIT EM | -/+ 10% for DALI | -/+ 15% for DALI & KIT EM

LIGHT DISTRIBUTION



SKU SPECIFICATIONS

Product Code	Dimensions (mm)	CCT (K)	Lumens (lm)	Power (W)	Eff. (lm/watt)	Lens Angle (°)
CRI 90						
1F9397 Stiletto J/3000/7W/90/A15/24V/Brass	Ø50 x H47mm ± 1mm	3000	420	7W	60	15°
1F9398 Stiletto J/3000/7W/90/A15/24V/White	Ø50 x H47mm ± 1mm	3000	420	7W	60	15°
1F9399 Stiletto J/3000/7W/90/A15/24V/Black	Ø50 x H47mm ± 1mm	3000	420	7W	60	15°
1F9400 Stiletto J/4000/7W/90/A15/24V/Brass	Ø50 x H47mm ± 1mm	4000	420	7W	60	15°
1F9401 Stiletto J/4000/7W/90/A15/24V/White	Ø50 x H47mm ± 1mm	4000	420	7W	60	15°
1F9402 Stiletto J/4000/7W/90/A15/24V/Black	Ø50 x H47mm ± 1mm	4000	420	7W	60	15°
1F9403 Stiletto J/6500/7W/90/A15/24V/Brass	Ø50 x H47mm ± 1mm	6500	420	7W	60	15°
1F9404 Stiletto J/6500/7W/90/A15/24V/White	Ø50 x H47mm ± 1mm	6500	420	7W	60	15°
1F9405 Stiletto J/6500/7W/90/A15/24V/Black	Ø50 x H47mm ± 1mm	6500	420	7W	60	15°
1F9406 Stiletto J/3000/7W/90/A24/24V/Brass	Ø50 x H47mm ± 1mm	3000	420	7W	60	24°
1F9407 Stiletto J/3000/7W/90/A24/24V/White	Ø50 x H47mm ± 1mm	3000	420	7W	60	24°
1F9408 Stiletto J/3000/7W/90/A24/24V/Black	Ø50 x H47mm ± 1mm	3000	420	7W	60	24°
1F9409 Stiletto J/4000/7W/90/A24/24V/Brass	Ø50 x H47mm ± 1mm	4000	420	7W	60	24°
1F9410 Stiletto J/4000/7W/90/A24/24V/White	Ø50 x H47mm ± 1mm	4000	420	7W	60	24°
1F9411 Stiletto J/4000/7W/90/A24/24V/Black	Ø50 x H47mm ± 1mm	4000	420	7W	60	24°
1F9412 Stiletto J/6500/7W/90/A24/24V/Brass	Ø50 x H47mm ± 1mm	6500	420	7W	60	24°
1F9413 Stiletto J/6500/7W/90/A24/24V/White	Ø50 x H47mm ± 1mm	6500	420	7W	60	24°
1F9414 Stiletto J/6500/7W/90/A24/24V/Black	Ø50 x H47mm ± 1mm	6500	420	7W	60	24°
1F9415 Stiletto J/3000/7W/90/A36/24V/Brass	Ø50 x H47mm ± 1mm	3000	420	7W	60	36°
1F9416 Stiletto J/3000/7W/90/A36/24V/White	Ø50 x H47mm ± 1mm	3000	420	7W	60	36°
1F9417 Stiletto J/3000/7W/90/A36/24V/Black	Ø50 x H47mm ± 1mm	3000	420	7W	60	36°
1F9418 Stiletto J/4000/7W/90/A36/24V/Brass	Ø50 x H47mm ± 1mm	4000	420	7W	60	36°
1F9419 Stiletto J/4000/7W/90/A36/24V/White	Ø50 x H47mm ± 1mm	4000	420	7W	60	36°
1F9420 Stiletto J/4000/7W/90/A36/24V/Black	Ø50 x H47mm ± 1mm	4000	420	7W	60	36°
1F9421 Stiletto J/6500/7W/90/A36/24V/Brass	Ø50 x H47mm ± 1mm	6500	420	7W	60	36°
1F9422 Stiletto J/6500/7W/90/A36/24V/White	Ø50 x H47mm ± 1mm	6500	420	7W	60	36°
1F9423 Stiletto J/6500/7W/90/A36/24V/Black	Ø50 x H47mm ± 1mm	6500	420	7W	60	36°
1F9424 Stiletto J/3000/7W/90/A50/24V/Brass	Ø50 x H47mm ± 1mm	3000	420	7W	60	50°
1F9425 Stiletto J/3000/7W/90/A50/24V/White	Ø50 x H47mm ± 1mm	3000	420	7W	60	50°
1F9426 Stiletto J/3000/7W/90/A50/24V/Black	Ø50 x H47mm ± 1mm	3000	420	7W	60	50°
1F9427 Stiletto J/4000/7W/90/A50/24V/Brass	Ø50 x H47mm ± 1mm	4000	420	7W	60	50°
1F9428 Stiletto J/4000/7W/90/A50/24V/White	Ø50 x H47mm ± 1mm	4000	420	7W	60	50°
1F9429 Stiletto J/4000/7W/90/A50/24V/Black	Ø50 x H47mm ± 1mm	4000	420	7W	60	50°
1F9430 Stiletto J/6500/7W/90/A50/24V/Brass	Ø50 x H47mm ± 1mm	6500	420	7W	60	50°
1F9431 Stiletto J/6500/7W/90/A50/24V/White	Ø50 x H47mm ± 1mm	6500	420	7W	60	50°
1F9432 Stiletto J/6500/7W/90/A50/24V/Black	Ø50 x H47mm ± 1mm	6500	420	7W	60	50°