



Zephyr Sphere 200

360° LIGHTING | DALI SERIES


- Zephyr 200 Sphere is a contemporary pendant light characterized by its sleek, spherical design. The globe-shaped diffuser emits a soft, ambient glow, which evenly distributes light in all directions and attracts a relaxed glaze towards the light source.
- The pendant is suspended by a stylish, fabric-covered cord, adding a touch of modern elegance and complementing various interior styles. Its minimalistic yet sophisticated design makes it suitable for a wide range of applications. This versatile luminaire is perfect for both commercial and residential settings, offering a blend of functionality and aesthetic appeal.


FEATURES & BENEFITS

- Lumen maintenance L90/B10@50.000h at 25°C
- IP45
- 5 years warranty
- · CRI90 as standard
- Efficiency@4000K 65 lm/W

APPLICATION

Grocery & Supermarkets | Retail | Office | Healthcare | Hospitality | DIY | Home






GREENTEK LIGHTING



SPECIFICATIONS

Power consumption	12W					
Dimensions	Ø200 x 199 ±1mm					
Housing materials	Aluminium, Glass					
IK code	IK07					
THD (at 230V, 50Hz, Full load)	-					
Protection class	Safety class 1					
Operating temperature [°C]	-20C+45C/-4F+113F					
Operating humidity [%]	10 ÷ 85					
Power factor	-					
DC Input [Vdc]	24 Vdc					
Lens angle [°]	313°					
Lifespan [h]	50000h					
Housing color	 Black NCS 9000-N Terra red NCS S 4040-Y70R Green NCS S 6005-G80Y White NCS 0502-G 					
Lumen maintenance	L90/B10@50.000h at 25°C					
IP factor	IP45					
Control optional	-					
Warranty [years]	5					
Storage temperature range [°C]	-20 ÷ +55					

LIGHT DISTRIBUTION



313°

GREENTEK LIGHTING 2



SKU SPECIFICATIONS

Product Code	Dimensions (mm)	CCT (K)	Lumens (Im)	Power (W)	Eff. (Im/watt)	Lens Angle
CRI90						
1G6012 Zephyr Sphere 200/2700/12W/90/B	Ø200±1mm	2700	890	12W	75	A313
1G6013 Zephyr Sphere 200/2700/12W/90/R	Ø200±1mm	2700	890	12W	75	A313
1G6014 Zephyr Sphere 200/2700/12W/90/GN	Ø200±1mm	2700	890	12W	75	A313
1G6015 Zephyr Sphere 200/2700/12W/90/W	Ø200±1mm	2700	890	12W	75	A313
1G6016 Zephyr Sphere 200/3000/12W/90/B	Ø200±1mm	3000	890	12W	75	A313
1G6017 Zephyr Sphere 200/3000/12W/90/R	Ø200±1mm	3000	890	12W	75	A313
1G6018 Zephyr Sphere 200/3000/12W/90/GN	Ø200±1mm	3000	890	12W	75	A313
1G6019 Zephyr Sphere 200/3000/12W/90/W	Ø200±1mm	3000	890	12W	75	A313
1G6020 Zephyr Sphere 200/4000/12W/90/B	Ø200±1mm	4000	890	12W	75	A313
1G6021 Zephyr Sphere 200/4000/12W/90/R	Ø200±1mm	4000	890	12W	75	A313
1G6022 Zephyr Sphere 200/4000/12W/90/GN	Ø200±1mm	4000	890	12W	75	A313
1G6023 Zephyr Sphere 200/4000/12W/90/W	Ø200±1mm	4000	890	12W	75	A313